

CHINA

CE ISO DE-P88

1PC

face to face PLASTIC WRAP

30 DAYS

DELLENT-PERKINS

500 PCS PER MONTH

Standby Power Perkins Diesel Generator 450kVA 50Hz 2206C-E13TAG3

Basic Information

- Place of Origin:
- Brand Name:
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:

Our Product Introduction

- Packaging Details:
- Delivery Time:
- Payment Terms: L/C, T/T
- Supply Ability:



Product Specification

Name:Brand:

Cooling System:

Frequency:Alternator:

• Engine Model:

• Prime Power:

• Highlight:

• Standby Power:

• Phase:

Type:Controller:

Perkins Diesel Generator 450kVA Perkins Water Cooling 50HZ Alternator Three Phase Diesel Generator Smartgen DSE 2206C-E13TAG3 320kVA/400kW 360kVA/450kW Standby Power Perkins Diesel Generator, Perkins Diesel Generator 450kVA,

Perkins 2206C-E13TAG3

High Light:

Commercial Perkins 450kVA Generator, 2206C-E13TAG3 Engine Diesel Generator, CE Perkins 450kva Generator, 50HZ

.PRODUCT DESCRIPTION

2206C-E13TAG3 50Hz 450kVA Standby Power Perkins Diesel Generator Set

Product Introduce:Dellent Power Perkins Series generator powered by the original Perkins engine, it enjoys high stability, reliability, durability, and long life with a wide range of power output. It is widely used in the area of the port, railway, industrial, and mining.





Product parameters:

| | DE-P450 |
|------------------|---|
| kVA | 450 |
| kW | 360 |
| kVA | 400 |
| kW | 320 |
| Hz | 50 |
| V | 400/230 |
| A | 577.4 |
| L | 600 |
| mm | 3500 X 1200 X 1960 |
| kg | 3480 |
| mm | 4350 X 1450 X 2180 |
| kg | 5260 |
| ^t dBA | 80 |
| • | Two of Free Maintenance Battery |
| | kW kVA kW Hz V A L L kg mm kg |

Engine Specification:

| Engine Manufacturer | | Perkins Engines Company Limited | |
|--------------------------|----|---|--|
| Engine Brand | | Perkins | |
| Engine Model | | 2206C-E13TAG3 | |
| No. of Cylinder | | 6 Cylinder in line | |
| Aspiration | | Turbocharged and Air to Air Aftercooled | |
| Governor | | Electric | |
| Engine Max. Output Power | kW | 413 | |
| Displacement | L | 12.5 | |

| Compression Ratio | | 16.3 : 1 | | |
|--|--------|----------------------|--|--|
| Starting Voltage | V | 24 | | |
| Bore | mm | 130 | | |
| Stroke | mm | 157 | | |
| Lubrication Oil Capacity | L | 38 | | |
| Intake Air Flow | M3/Min | 12.5 | | |
| Fuel Consumption at 100% Load | L/H | 85 | | |
| Specification of Control Panel: Control Panel Specification | | | | |
| Controller Brand | | Smartgen | | |
| Breaker Brand | | Delixi | | |
| Breaker Capacity (A) | | 630 | | |
| Emergency Stop Button | | Supply | | |
| Automatic Mains Fail (AMF) | | Supply | | |
| Fuel Level | | Supply | | |
| Automatic Transfer Switch | | ATS as optional part | | |

The control panel supply the full protection with alarm and shutdown of the diesel generator include Start-up fault (generator set shutdown), High coolant temperature (alarm and generator set shutdown), Low oil pressure (alarm and generator set shutdown), Low fuel level (alarm), Low cooling fluid level alarm (as optional), Overload (alarm and generator set shutdown), Battery voltage high (alarm).

Optional controller: Each model of Deepsea, Smartgen, ComAp brand controller.





NO.7, JINYE ROADTIEHU INDUSTRIAL AREA CHENGYANG TOWN, FUAN CITY, NINGDECITY, FUJIAN.CHINA