



DE-IS28 Isuzu Diesel Generator 20kW 25kva 3 Phase Generator With Low Fuel Consumption

Our Product Introduction

Basic Information

- Place of Origin: CHINA
- Brand Name: DELLENT-ISUZU
- Certification: CE ISO
- Model Number: DE-IS28
- Minimum Order Quantity: 1*20GP
- Price: face to face
- Packaging Details: PLASTIC WRAP
- Delivery Time: 20-30 DAYS
- Payment Terms: L/C, T/T
- Supply Ability: 500 PCS PER MONTH



Product Specification

- Name: Isuzu Diesel Generator
- Brand: ISUZU
- Cooling System: Water Cooling
- Frequency: 50Hz
- Alternator: Tamford/ Leroy Somer/ Mecc Alte
- Controller Model: Deepsea/ ComAp/Smartgen
- Phase: Three Phase
- Type: Diesel Generator
- Controller: Smartgen DSE
- Engine Model: JE493DB-02
- Prime Power: 25kVA/20kW
- Standby Power: 27.5kVA/22kW
- Highlight: **Isuzu Diesel Generator 25kVA,
Isuzu Diesel Generator 20kW,
25kva 3 Phase Generator**

for more products please visit us on dellentpower.com

Product Description

Commercial ISUZU 25kVA Generator ,JE493DB-02 Engine Diesel Generator ,
Light: CE ISUZU 25kVA Generator ,50HZ

.PRODUCT DESCRIPTION

Product Introduce:

Our Isuzu engine diesel generator have all series from 20kva to 106kva. Isuzu diesel engine which features reliable starting performance, environmental protection, low vibration, and energy-saving, etc. Benefiting from the engine's characteristics, the Isuzu diesel generator set features stable and reliable work at running.

Application fields:

Diesel generator are used in any situation where a reliable backup power source is necessary to maintain continuity of operations.

For example:

Healthcare, Data Centers, Telecommunications, Construction, Manufacturing, Oil and Gas, Military, Residential electricity.

Advantage :

Isuzu diesel engine which features reliable starting performance, environmental protection, low vibration, and energy-saving, etc. Benefiting from the engine's characteristics, the Isuzu diesel generator set features stable and reliable work at running.

Product parameters:

Specification:

Model		DE-IS28
Max. Power	kVA	28
	kW	22.4
Rate Power	kVA	25
	kW	20
Frequency	Hz	50
Rate Voltage	V	400/230
Rate Current	A	36.1
Fuel Tank Capacity	L	60

Technical Data of ISUZU Diesel Engine:

Engine Specification		
Engine Manufacturer		Jiangxi Isuzu Motors Co., Ltd.
Engine Brand		Isuzu
Engine Model		JE493DB-02
No. of Cylinder		4 Cylinder in line
Aspiration		Naturally Aspirated
Governor		Electric
Engine Max. Output Power	kW	27
Displacement	L	2.7
Compression Ratio		18.2 : 1
Starting Voltage	V	12
Bore	mm	93
Stroke	mm	102
Lubrication Oil Capacity	L	5.6
Intake Air Flow	L/S	33
Fuel Consumption at 100% Load	L/H	6.3

Control Panel Specification:

Controller Brand	Smartgen
Breaker Brand	Delixi
Breaker Capacity (A)	63
Battery Charger	Smartgen

Emergency Stop Button	Supply
Automatic Mains Fail (AMF)	Supply
Fuel Level	Supply
Automatic Transfer Switch	ATS as optional part
The control panel supply the full protection with alarm and shutdown of the diesel generator include Start-up fault (generator set shutdown), High coolant temperature (alarm and generator set shutdown), Low oil pressure (alarm and generator set shutdown), Low fuel level (alarm), Low cooling fluid level alarm (as optional), Overload (alarm and generator set shutdown), Battery voltage high (alarm).	
Optional controller: Each model of Deepsea, Smartgen, ComAp brand controller.	

. Why Choose Us:

Dedicated
We are DEDICATED to meet Customers' need.

Enthusiasm
We respond to our Customers' ENTHUSIASM

Loyalty
We cherish our Customers' LOYALTY

Luxury
We aim to establish our own LUXURY brand

Efficient
We offer our EFFICIENT service

Newest
We adopt NEWEST technologies for products

Trust
We strive for winning the TRUST from Customers

. QUALIFICATION CERTIFICATE:



. FACTORY INTERIOR:



If you need ISUZU generator with other models technical data, kindly contact us for catalogues!



Fuan Dellent Electric & Machinery Co., Ltd.



+8613706938606



jennifer@dellent.com



dellentpower.com

NO.7,JINYE ROADTIEHU INDUSTRIAL AREA CHENGYANG TOWN, FUAN
CITY,NINGDECITY,FUJIAN.CHINA