



Water Cooled 50KW Diesel Generator Cummins Genset 50HZ / 60HZ

Our Product Introduction

Basic Information

- Place of Origin: CHINA
- Brand Name: DELLENT
- Certification: CE/ISO9001
- Model Number: DE-C22~C66
- Minimum Order Quantity: 1 PC
- Price: bargain face-to-face
- Packaging Details: PLASTIC WRAP OR PLYWOOD CASE
- Delivery Time: 20-30 DAYS
- Payment Terms: L/C, T/T
- Supply Ability: 1 MONTH 600PCS



Product Specification

- Name: 50KW Diesel Generator Cummins
- Engine Brand: Cummins
- Cooling Method: Water-Cooling System
- Fuel Type: Diesel
- Rated Frequency: 50HZ/60HZ
- Speed: 1500RPM/1800RPM
- Warranty: 12 Months/1000 Hours
- Highlight: **50KW Diesel Generator Cummins, 50kw Cummins Generator, Cummins Genset**

for more products please visit us on dellentpower.com

CE Cummins Diesel Generator about 50kW.

Our Cummins diesel generators are known for their durability, fuel efficiency, and low maintenance requirements. With Cummins engines at their core, these generators offer reliable power output that can be trusted for a range of applications. From backup power for homes and businesses to powering construction sites and events, our Cummins diesel generators deliver the power you need when you need it.

We also prioritize ease of use and maintenance for our customers. Our generators are designed with a user-friendly interface and easy access to key components for maintenance and repairs. Regular maintenance is essential for the longevity and optimal performance of your generator, and our team can provide support and guidance for creating a maintenance schedule that suits your specific needs.

. PRODUCT

50-60 Hz TECHNICAL DATA											
Model	Rated Power (kW)	Rated Power (kVA)	Rated Voltage (V)	Rated Frequency (Hz)	Rated Speed (rpm)	Rated Current (A)	Rated Power (kW)	Rated Power (kVA)	Rated Voltage (V)	Rated Frequency (Hz)	Rated Speed (rpm)
DC-020	20	22.3	24	50	1500	48.4	20	22.3	24	50	1500
DC-025	25	27.5	24	50	1500	58.3	25	27.5	24	50	1500
DC-030	30	33	24	50	1500	69.3	30	33	24	50	1500
DC-035	35	38.5	24	50	1500	80.9	35	38.5	24	50	1500
DC-040	40	44	24	50	1500	92.4	40	44	24	50	1500
DC-045	45	49.5	24	50	1500	104	45	49.5	24	50	1500
DC-050	50	55	24	50	1500	115.5	50	55	24	50	1500
DC-055	55	60.5	24	50	1500	127	55	60.5	24	50	1500
DC-060	60	66	24	50	1500	138.5	60	66	24	50	1500
DC-065	65	71.5	24	50	1500	150	65	71.5	24	50	1500
DC-070	70	77	24	50	1500	161.5	70	77	24	50	1500
DC-075	75	82.5	24	50	1500	173	75	82.5	24	50	1500
DC-080	80	88	24	50	1500	184.5	80	88	24	50	1500
DC-085	85	93.5	24	50	1500	196	85	93.5	24	50	1500
DC-090	90	99	24	50	1500	207.5	90	99	24	50	1500
DC-095	95	104.5	24	50	1500	219	95	104.5	24	50	1500
DC-100	100	110	24	50	1500	230.5	100	110	24	50	1500
DC-105	105	115.5	24	50	1500	242	105	115.5	24	50	1500
DC-110	110	121	24	50	1500	253.5	110	121	24	50	1500
DC-115	115	126.5	24	50	1500	265	115	126.5	24	50	1500
DC-120	120	132	24	50	1500	276.5	120	132	24	50	1500
DC-125	125	137.5	24	50	1500	288	125	137.5	24	50	1500
DC-130	130	143	24	50	1500	299.5	130	143	24	50	1500
DC-135	135	148.5	24	50	1500	311	135	148.5	24	50	1500
DC-140	140	154	24	50	1500	322.5	140	154	24	50	1500
DC-145	145	159.5	24	50	1500	334	145	159.5	24	50	1500
DC-150	150	165	24	50	1500	345.5	150	165	24	50	1500
DC-155	155	170.5	24	50	1500	357	155	170.5	24	50	1500
DC-160	160	176	24	50	1500	368.5	160	176	24	50	1500
DC-165	165	181.5	24	50	1500	380	165	181.5	24	50	1500
DC-170	170	187	24	50	1500	391.5	170	187	24	50	1500
DC-175	175	192.5	24	50	1500	403	175	192.5	24	50	1500
DC-180	180	198	24	50	1500	414.5	180	198	24	50	1500
DC-185	185	203.5	24	50	1500	426	185	203.5	24	50	1500
DC-190	190	209	24	50	1500	437.5	190	209	24	50	1500
DC-195	195	214.5	24	50	1500	449	195	214.5	24	50	1500
DC-200	200	220	24	50	1500	460.5	200	220	24	50	1500
DC-205	205	225.5	24	50	1500	472	205	225.5	24	50	1500
DC-210	210	231	24	50	1500	483.5	210	231	24	50	1500
DC-215	215	236.5	24	50	1500	495	215	236.5	24	50	1500
DC-220	220	242	24	50	1500	506.5	220	242	24	50	1500
DC-225	225	247.5	24	50	1500	518	225	247.5	24	50	1500
DC-230	230	253	24	50	1500	529.5	230	253	24	50	1500
DC-235	235	258.5	24	50	1500	541	235	258.5	24	50	1500
DC-240	240	264	24	50	1500	552.5	240	264	24	50	1500
DC-245	245	269.5	24	50	1500	564	245	269.5	24	50	1500
DC-250	250	275	24	50	1500	575.5	250	275	24	50	1500
DC-255	255	280.5	24	50	1500	587	255	280.5	24	50	1500
DC-260	260	286	24	50	1500	598.5	260	286	24	50	1500
DC-265	265	291.5	24	50	1500	610	265	291.5	24	50	1500
DC-270	270	297	24	50	1500	621.5	270	297	24	50	1500
DC-275	275	302.5	24	50	1500	633	275	302.5	24	50	1500
DC-280	280	308	24	50	1500	644.5	280	308	24	50	1500
DC-285	285	313.5	24	50	1500	656	285	313.5	24	50	1500
DC-290	290	319	24	50	1500	667.5	290	319	24	50	1500
DC-295	295	324.5	24	50	1500	679	295	324.5	24	50	1500
DC-300	300	330	24	50	1500	690.5	300	330	24	50	1500
DC-305	305	335.5	24	50	1500	702	305	335.5	24	50	1500
DC-310	310	341	24	50	1500	713.5	310	341	24	50	1500
DC-315	315	346.5	24	50	1500	725	315	346.5	24	50	1500
DC-320	320	352	24	50	1500	736.5	320	352	24	50	1500
DC-325	325	357.5	24	50	1500	748	325	357.5	24	50	1500
DC-330	330	363	24	50	1500	759.5	330	363	24	50	1500
DC-335	335	368.5	24	50	1500	771	335	368.5	24	50	1500
DC-340	340	374	24	50	1500	782.5	340	374	24	50	1500
DC-345	345	379.5	24	50	1500	794	345	379.5	24	50	1500
DC-350	350	385	24	50	1500	805.5	350	385	24	50	1500
DC-355	355	390.5	24	50	1500	817	355	390.5	24	50	1500
DC-360	360	396	24	50	1500	828.5	360	396	24	50	1500
DC-365	365	401.5	24	50	1500	840	365	401.5	24	50	1500
DC-370	370	407	24	50	1500	851.5	370	407	24	50	1500
DC-375	375	412.5	24	50	1500	863	375	412.5	24	50	1500
DC-380	380	418	24	50	1500	874.5	380	418	24	50	1500
DC-385	385	423.5	24	50	1500	886	385	423.5	24	50	1500
DC-390	390	429	24	50	1500	897.5	390	429	24	50	1500
DC-395	395	434.5	24	50	1500	909	395	434.5	24	50	1500
DC-400	400	440	24	50	1500	920.5	400	440	24	50	1500
DC-405	405	445.5	24	50	1500	932	405	445.5	24	50	1500
DC-410	410	451	24	50	1500	943.5	410	451	24	50	1500
DC-415	415	456.5	24	50	1500	955	415	456.5	24	50	1500
DC-420	420	462	24	50	1500	966.5	420	462	24	50	1500
DC-425	425	467.5	24	50	1500	978	425	467.5	24	50	1500
DC-430	430	473	24	50	1500	989.5	430	473	24	50	1500
DC-435	435	478.5	24	50	1500	1001	435	478.5	24	50	1500
DC-440	440	484	24	50	1500	1012.5	440	484	24	50	1500
DC-445	445	489.5	24	50	1500	1024	445	489.5	24	50	1500
DC-450	450	495	24	50	1500	1035.5	450	495	24	50	1500
DC-455	455	500.5	24	50	1500	1047	455	500.5	24	50	1500
DC-460	460	506	24	50	1500	1058.5	460	506	24	50	1500
DC-465	465	511.5	24	50	1500	1070	465	511.5	24	50	1500
DC-470	470	517	24	50	1500	1081.5	470	517	24	50	1500
DC-475	475	522.5	24	50	1500	1093	475	522.5	24	50	1500
DC-480	480	528	24	50	1500	1104.5	480	528	24	50	1500
DC-485	485	533.5	24	50	1500	1116	485	533.5	24	50	1500
DC-490	490	539	24	50	1500	1127.5	490	539	24	50	1500
DC-495	495	544.5	24	50	1500	1139	495	544.5	24	50	1500
DC-500	500	550	24	50	1500	1150.5	500	550	24	50	1500

. Why Choose Us:

Dedicated
We are DEDICATED to meet Customers' need.

Enthusiasm
We respond to our Customers' ENTHUSIASM

Loyalty
We cherish our Customers' LOYALTY

Luxury
We aim to establish our own LUXURY brand

Efficient
We offer our EFFICIENT service

Newest
We adopt NEWEST technologies for products

Trust
We strive for winning the TRUST from Customers

. QUALIFICATION CERTIFICATE:



. FACTORY INTERIOR:



FAQ

Q: What's your delivery time?

A: Standard product 20 days - 30 days.

Q: Can we add our logo to products?

A: Yes, there are several ways to do this. We can put the label of your logo on the products or make the silk print of your logo on the products. It is free.

Q: Can we customize the product?

A: We have a very experienced technical team, we can customize any product according to your requirements, such as synchronization system, wet exhaust system, ultra-silent system



Fuan Dellent Electric & Machinery Co., Ltd.

+8613706938606

jennifer@dellent.com

dellentpower.com

NO.7,JINYE ROADTIEHU INDUSTRIAL AREA CHENGYANG TOWN, FUAN
CITY,NINGDE CITY,FUJIAN,CHINA